EMOMIJI PRECISION CONDUCTIVE PLASTIC POTENTIOMETER

RCP-32FB SERIES



RCP-32FB

■ PRODUCT FEATURES

- 360° Non-stop Rotation;
- Built-in Ball Bearing;
- Light Weight,Low Cost;
- Tailor-made Specification Wellcome.

■ PARAMETER

MODEL	RCP-32FB-30RS	RCP-32FB-40RS
L	30	40

■ ELECTRICAL CHARACTERISTICS

Effective Electrical Angle	290°
Total Resistance Value	0.5、1、2、5、10kΩ
Total Resistance Tolerance	±20%
Independent Linearity	±1% (±0.2% Precision)
Power Rating	2W/70℃
Output Smoothness	0.1% Max
Insulation Resistance	Max 100MΩ at DC1000V
Dielectric strength	AC1000V For 1 Minute
Resistance of Temperature Coefficient	±500ppm/℃

■ MECHANICAL CHARACTERISTICS

Mechanical Rotation Angle	360° Non-stop
Rotational Torque	18×10^{-4}N.m (18gf.cm) Max
Weight	About 40g

■ ENVIRONMENTAL CHARACTERISTICS

Operating Temperature Range	−40~120℃
Vibration	150m/s² (15G) 2000Hz
Shock	490m/s² (50G) 11ms
Life Cycle	10 million cycles

■ OUTLINE DRAWING



■ MOUNTING DIAGRAM



■ CIRCUIT CONNECTION





Mounting Side View

■ OUTPUT CHARACTERISTICS



Effective Electrical Angle

China Head office : East Momiji Precision Co., Limited URL : www.emomiji.com E-mail : info@emomiji.com
Poland Branch Office : Trim-pot., URL : www.trim-pot.com.pl E-mail : biuro@trim-pot.com.pl Tel : 0048 (12) 387-06-01 Fax : 0048 (12) 387-06-02