

Czujnik Temperatury W 13

Zastosowanie:

-ICE, urządzenia klimatyzacyjne

Dane techniczne

Czujnik	NTC 5K3A	
Szczelnosc czujnika	Odpornosc na wilgotn.	
Zakres temp. °C	-40 do +70	
R ₂₅ Ω	5 .000	
Zaciski	1-2	
Przewod	2X0,5 albo 2X0,75 mm ²	
Tuleja	MS	
Uszczelka	GDM3-17	
Obudowa gniazda	GDM	
Obudowa	Hirschmann 12BGDM	
Wymiary (mm)	90X50	

°C	0	1	2	3	4	5	6	7	8	9	10
-20	48536	51450	54550	57850	61400	65200	69250	73600	78200	83150	88500
-10	27665	29215	30865	32620	34490	36475	38590	40845	43245	45805	48536
-0	16325	17185	18095	19055	20080	21165	22310	23530	24825	26200	27665
0	16325	15515	14750	14025	13245	12695	12085	11585	10960	10440	9950
10	9950	9485	9045	8625	8230	7855	7500	7160	6840	6636	6245
20	6245	5970,0	5720,0	5460,0	5225,0	5000,0	4786,5	4583,5	4388,5	4203,5	4028,5
30	4028,6	3861,5	3701,5	3548,5	3403,5	3265,0	3133,5	3008,5	2888,5	2776,5	2663,3
40	2663,3	2558,5	2468,5	2363,5	2277,5	2185,0	2100,5	2020,0	1945,0	1871,5	1801,5
50	1801,5	1733,5	1670,0	1608,5	1549,5	1493,0	1439,0	1387,0	1337,5	1289,5	1244,0
60	1244,0	1200,0	1158,0	1117,5	1078,5	1041,5	1005,5	971,0	938,0	906,5	876,0
70	876,0	846,5	818,0	791,0	766,0	739,0	715,5	692,0	670,0	648,5	627,5
80	627,50	607,50	588,50	570,00	552,00	535,00	518,00	502,00	486,85	472,00	457,65
90	457,65	443,85	430,50	417,65	406,15	393,35	381,65	370,50	359,65	349,35	339,15
100	339,15	329,50	320,15	311,00	302,15	293,65	285,50	277,50	269,85	262,50	255,15
110	255,15	248,35	241,50	235,00	228,65	222,50	216,65	210,85	206,35	200,00	194,65
120	194,65	189,65	184,85	180,00	175,30	170,85	166,55	162,35	158,25	154,30	150,47