


06,07 Series Tact Switches (SMD,Taping, Tape & Reel optional)




SPECIFICATION:

Rating : DC 12V 50mA	Mechanical Life : 1,000,000 cycles
Insulation Resistance : > 100M Ω DC250V	Electrical Life : 100,000 cycles
Withstand Voltage : AC250V 1minute	Ambient Temper. Used : -25°C to +70°C
Contact Resistance : < 100m Ω	Ambient Humidity Used : < 85% RH
Soldering Temper : < 255°C max, 5sec	Operating Force : 130, 160 $\pm$ 30g or 250 $\pm$ 50g

0643,0650




MODEL NO.	H
0643	4.3
0650	5.0




SCHEMATIC




P.C.B. HOLE DETAIL





0670, 0680, 0695
0612, 0613, 0617



MODEL NO.	H
0670	7.0
0680	8.0
0695	9.5
0612	12
0613	13
0617	17




Special : 06125, H=12.5
06135, H=13.5




SCHEMATIC



P.C.B. HOLE DETAIL



0673







Cap: C

4

R


5



SCHEMATIC






P.C.B. HOLE DETAIL



0643G (Grounding)
0650G



MODEL NO.	H
0643G	4.3
0650G	5.0



SCHEMATIC



P.C.B. HOLE DETAIL

